

MGS 2011: FUN Lecture 4

More about Monads

Henrik Nilsson

University of Nottingham, UK

This Lecture

- Monads in Haskell
- Some standard monads
- Combining effects: monad transformers

Monads in Haskell

In Haskell, the notion of a monad is captured by a **Type Class**:

```
class Monad m where
    return :: a -> m a
    (>>=)  :: m a -> (a -> m b) -> m b
```

Allows names of the common functions to be overloaded and sharing of derived definitions.

The Maybe Monad in Haskell

```
instance Monad Maybe where
    -- return :: a -> Maybe a
    return = Just

    -- (>>=) :: Maybe a -> (a -> Maybe b)
    --                -> Maybe b
    Nothing  >>= _ = Nothing
    (Just x) >>= f = f x
```

Exercise 1: A State Monad in Haskell

Haskell 98 does not permit type synonyms to be instances of classes. Hence we have to define a new type:

```
newtype S a = S (Int -> (a, Int))
```

```
unS :: S a -> (Int -> (a, Int))
```

```
unS (S f) = f
```

Provide a Monad instance for S.

Exercise 1: Solution

```
instance Monad S where  
    return a = S (\s -> (a, s))
```

```
m >>= f = S $ \s ->  
    let (a, s') = unS m s  
    in unS (f a) s'
```

Monad-specific Operations (1)

To be useful, monads need to be equipped with additional operations specific to the effects in question. For example:

```
fail :: String -> Maybe a
fail s = Nothing
```

```
catch :: Maybe a -> Maybe a -> Maybe a
m1 `catch` m2 =
  case m1 of
    Just _   -> m1
    Nothing -> m2
```

Monad-specific Operations (2)

Typical operations on a state monad:

```
set :: Int -> S ()  
set a = S (\_ -> ((), a))
```

```
get :: S Int  
get = S (\s -> (s, s))
```

Moreover, need to “run” a computation. E.g.:

```
runS :: S a -> a  
runS m = fst (unS m 0)
```


The `do`-notation (1)

Haskell provides convenient syntax for programming with monads:

```
do
```

```
  a <- exp1
```

```
  b <- exp2
```

```
  return exp3
```

is syntactic sugar for

```
exp1 >>= \a ->
```

```
exp2 >>= \b ->
```

```
return exp3
```

The **do**-notation (2)

Computations can be done solely for effect, ignoring the computed value:

```
do
   $exp_1$ 
   $exp_2$ 
  return  $exp_3$ 
```

is syntactic sugar for

```
 $exp_1$  >>= \_ ->
 $exp_2$  >>= \_ ->
return  $exp_3$ 
```

The `do`-notation (3)

A `let`-construct is also provided:

```
do
  let a =  $exp_1$ 
      b =  $exp_2$ 
  return  $exp_3$ 
```

is equivalent to

```
do
  a <- return  $exp_1$ 
  b <- return  $exp_2$ 
  return  $exp_3$ 
```

Numbering Trees in do-notation

```
numberTree :: Tree a -> Tree Int
```

```
numberTree t = runS (ntAux t)
```

```
  where
```

```
    ntAux :: Tree a -> S (Tree Int)
```

```
    ntAux (Leaf _) = do
```

```
      n <- get
```

```
      set (n + 1)
```

```
      return (Leaf n)
```

```
    ntAux (Node t1 t2) = do
```

```
      t1' <- ntAux t1
```

```
      t2' <- ntAux t2
```

```
      return (Node t1' t2')
```

The Compiler Fragment Revisited (1)

Given a suitable “Diagnostics” monad \mathbb{D} that collects error messages, `enterVar` can be turned from this:

```
enterVar :: Id -> Int -> Type -> Env  
         -> Either Env ErrorMgs
```

into this:

```
enterVarD :: Id -> Int -> Type -> Env  
          -> D Env
```

and then `identDefs` from this ...

The Compiler Fragment Revisited (2)

```
identDefs l env [] = ([], env, [])
identDefs l env ((i,t,e) : ds) =
  ((i,t,e') : ds', env'', ms1++ms2++ms3)
  where
    (e', ms1) = identAux l env e
    (env', ms2) =
      case enterVar i l t env of
        Left env'  -> (env', [])
        Right m    -> (env, [m])
    (ds', env'', ms3) =
      identDefs l env' ds
```

The Compiler Fragment Revisited (3)

into this:

```
identDefsD l env [] = return ([], env)
identDefsD l env ((i,t,e) : ds) = do
    e'      <- identAuxD l env e
    env'     <- enterVarD i l t env
    (ds', env'') <- identDefsD l env' ds
    return ((i,t,e') : ds', env'')
```

(Suffix D just to remind us the types have changed.)

The Compiler Fragment Revisited (4)

Compare with the “core” identified earlier!

```
identDefs l env [] = ([], env)
identDefs l env ((i,t,e) : ds) =
  ((i,t,e') : ds', env'')
  where
    e'          = identAux l env e
    env'         = enterVar i l t env
    (ds', env'') = identDefs l env' ds
```

The monadic version is very close to ideal,
without sacrificing functionality, clarity, or
pureness!

The List Monad

Computation with many possible results,
“nondeterminism”:

```
instance Monad [] where
    return a = [a]
    m >>= f  = concat (map f m)
    fail s   = []
```

Example:

```
x <- [1, 2]
y <- ['a', 'b']
return (x,y)
```

Result:

```
[(1, 'a'), (1, 'b'),
 (2, 'a'), (2, 'b')]
```

The Reader Monad

Computation in an environment:

```
instance Monad ((->) e) where
    return a = const a
    m >>= f  = \e -> f (m e) e
```

```
getEnv :: ((->) e) e
getEnv = id
```

The Haskell IO Monad

In Haskell, IO is handled through the IO monad. IO is **abstract**! Conceptually:

```
newtype IO a = IO (World -> (a, World))
```

Some operations:

```
putChar      :: Char -> IO ()
putStr       :: String -> IO ()
putStrLn     :: String -> IO ()
getChar      :: IO Char
getLine      :: IO String
getContents  :: IO String
```

Monad Transformers (1)

What if we need to support more than one type of effect?

Monad Transformers (1)

What if we need to support more than one type of effect?

For example: State and Error/Partiality?

Monad Transformers (1)

What if we need to support more than one type of effect?

For example: State and Error/Partiality?

We could implement a suitable monad from scratch:

```
newtype SE s a = SE (s -> Maybe (a, s))
```

-
-
-

Monad Transformers (2)

However:

Monad Transformers (2)

However:

- Not always obvious how: e.g., should the combination of state and error have been

```
newtype SE s a = SE (s -> (Maybe a, s))
```


Monad Transformers (2)

However:

- Not always obvious how: e.g., should the combination of state and error have been

```
newtype SE s a = SE (s -> (Maybe a, s))
```

- Duplication of effort: similar patterns related to specific effects are going to be repeated over and over in the various combinations.

Monad Transformers (3)

Monad Transformers can help:

Monad Transformers (3)

Monad Transformers can help:

- A **monad transformer** transforms a monad by adding support for an additional effect.

Monad Transformers (3)

Monad Transformers can help:

- A **monad transformer** transforms a monad by adding support for an additional effect.
- A library of monad transformers can be developed, each adding a specific effect (state, error, ...), allowing the programmer to mix and match.

Monad Transformers (3)

Monad Transformers can help:

- A **monad transformer** transforms a monad by adding support for an additional effect.
- A library of monad transformers can be developed, each adding a specific effect (state, error, ...), allowing the programmer to mix and match.
- A form of **aspect-oriented programming**.

Monad Transformers in Haskell (1)

- A *monad transformer* maps monads to monads. Represented by a type constructor T of the following kind:

$$T :: (* \rightarrow *) \rightarrow (* \rightarrow *)$$

Monad Transformers in Haskell (1)

- A **monad transformer** maps monads to monads. Represented by a type constructor `T` of the following kind:

$$T :: (* \rightarrow *) \rightarrow (* \rightarrow *)$$

- Additionally, a monad transformer **adds** computational effects. A mapping `lift` from computations in the underlying monad to computations in the transformed monad is needed:

$$\text{lift} :: M\ a \rightarrow T\ M\ a$$

Monad Transformers in Haskell (2)

- These requirements are captured by the following (multi-parameter) type class:

```
class (Monad m, Monad (t m))  
      => MonadTransformer t m where  
  lift :: m a -> t m a
```


Classes for Specific Effects

A monad transformer adds specific effects to *any* monad. Thus the effect-specific operations needs to be overloaded. For example:

```
class Monad m => E m where
    eFail :: m a
    eHandle :: m a -> m a -> m a
```

```
class Monad m => S m s | m -> s where
    sSet :: s -> m ()
    sGet :: m s
```

The Identity Monad

We are going to construct monads by successive transformations of the identity monad:

```
newtype I a = I a
```

```
unI (I a) = a
```

```
instance Monad I where
```

```
    return a = I a
```

```
    m >>= f = f (unI m)
```

```
runI :: I a -> a
```

```
runI = unI
```

The Error Monad Transformer (1)

```
newtype ET m a = ET (m (Maybe a))  
unET (ET m) = m
```

Any monad transformed by ET is a monad:

```
instance Monad m => Monad (ET m) where  
    return a = ET (return (Just a))
```

```
    m >>= f = ET $ do  
        ma <- unET m  
        case ma of  
            Nothing -> return Nothing  
            Just a   -> unET (f a)
```

The Error Monad Transformer (2)

We need the ability to run transformed monads:

```
runET :: Monad m => ET m a -> m a
runET etm = do
    ma <- unET etm
    case ma of
        Just a   -> return a
        Nothing  -> error "Should not happen"
```

ET is a monad transformer:

```
instance Monad m =>
    MonadTransformer ET m where
    lift m = ET (m >>= \a -> return (Just a))
```

The Error Monad Transformer (3)

Any monad transformed by `ET` is an instance of `E`:

```
instance Monad m => E (ET m) where
    eFail = ET (return Nothing)
    m1 `eHandle` m2 = ET $ do
        ma <- unET m1
        case ma of
            Nothing -> unET m2
            Just _   -> return ma
```

The Error Monad Transformer (4)

A state monad transformed by ET is a state monad:

```
instance S m s => S (ET m) s where
    sSet s = lift (sSet s)
    sGet = lift sGet
```

Exercise 2: Running Transf. Monads

Let

```
ex2 = eFail `eHandle` return 1
```

1. Suggest a possible type for `ex2`.
(Assume `1 :: Int`.)
2. Given your type, use the appropriate combination of “run functions” to run `ex2`.

Exercise 2: Solution

```
ex2 :: ET I Int
```

```
ex2 = eFail `eHandle` return 1
```

```
ex2result :: Int
```

```
ex2result = runI (runET ex2)
```


The State Monad Transformer (1)

```
newtype ST s m a = ST (s -> m (a, s))
unST (ST m) = m
```

Any monad transformed by ST is a monad:

```
instance Monad m => Monad (ST s m) where
    return a = ST (\s -> return (a, s))
```

```
m >>= f = ST $ \s -> do
    (a, s') <- unST m s
    unST (f a) s'
```

The State Monad Transformer (2)

We need the ability to run transformed monads:

```
runST :: Monad m => ST s m a -> s -> m a
runST stf s0 = do
    (a, _) <- unST stf s0
    return a
```

ST is a monad transformer:

```
instance Monad m =>
    MonadTransformer (ST s) m where
    lift m = ST (\s -> m >>= \a ->
        return (a, s))
```

The State Monad Transformer (3)

Any monad transformed by ST is an instance of S:

```
instance Monad m => S (ST s m) s where
    sSet s = ST (\_ -> return ((), s))
    sGet   = ST (\s -> return (s, s))
```

An error monad transformed by ST is an error monad:

```
instance E m => E (ST s m) where
    eFail = lift eFail
    m1 `eHandle` m2 = ST $ \s ->
        unST m1 s `eHandle` unST m2 s
```

Exercise 3: Effect Ordering

Consider the code fragment

```
ex3a :: (ST Int (ET I)) Int
ex3a = (sSet 42 >> eFail) `eHandle` sGet
```

Note that the exact same code fragment also can be typed as follows:

```
ex3b :: (ET (ST Int I)) Int
ex3b = (sSet 42 >> eFail) `eHandle` sGet
```

What is

```
runI (runET (runST ex3a 0))
runI (runST (runET ex3b) 0)
```

Exercise 3: Solution

`runI (runET (runST ex3a 0)) = 0`

`runI (runST (runET ex3b) 0) = 42`

Why? Because:

$$\begin{aligned} \text{ST } s \text{ (ET } I) \text{ } a &\models s \rightarrow (\text{ET } I) (a, s) \\ &\models s \rightarrow I (\text{Maybe } (a, s)) \\ &\models s \rightarrow \text{Maybe } (a, s) \\ \text{ET } (\text{ST } s \text{ } I) \text{ } a &\models (\text{ST } s \text{ } I) (\text{Maybe } a) \\ &\models s \rightarrow I (\text{Maybe } a, s) \\ &\models s \rightarrow (\text{Maybe } a, s) \end{aligned}$$

Exercise 4: Alternative ST?

To think about.

Could ST have been defined in some other way,
e.g.

```
newtype ST s m a = ST (m (s -> (a, s)))
```

or perhaps

```
newtype ST s m a = ST (s -> (m a, s))
```

Problems with Monad Transformers

- With one transformer for each possible effect, we get a lot of combinations: the number grows quadratically; each has to be instantiated explicitly.
- Jaskelioff (2008,2009) has proposed a possible, more extensible alternative.

Reading (1)

- Nick Benton, John Hughes, Eugenio Moggi. Monads and Effects. In *International Summer School on Applied Semantics 2000*, Caminha, Portugal, 2000.
- Sheng Liang, Paul Hudak, Mark Jones. Monad Transformers and Modular Interpreters. In *Proceedings of the 22nd ACM Symposium on Principles of Programming Languages (POPL'95)*, January 1995, San Francisco, California

Reading (2)

- Mauro Jaskelioff. Monatron: An Extensible Monad Transformer Library. In *Implementation of Functional Languages (IFL'08)*, 2008.
- Mauro Jaskelioff. Modular Monad Transformers. In *European Symposium on Programming (ESOP,09)*, 2009.